

&lt; FOR REFERENCE &gt;

---

---

## SPECIFICATION

---

---

Name	UPS SYSTEM
Model	ALS-1.5KHRM
Spec. No.	

株式会社 **YAMABISHI**  
YAMABISHI Corporation

## 1. CVCF specifications

- 1) Model : ALS-1.5KHRM
- 2) UPS Type : On-Line Type
- 3) Rating : Continuous
- 4) Backup time : 6 minut (Power factor 0.7)
- 5) AC input
  - a. Phase : Single Phase 2 Wire
  - b. Frequency : 50/60Hz
  - c. Voltage : 170~265V
- 6) AC output
  - a. Capacity : 1.5kVA/1050W
  - b. Phase : Single Phase 2 Wire
  - c. Voltage : 200/220/230/240V (Selection type)
  - d. Voltage accuracy : within  $\pm 3\%$
  - e. Frequency : 50/60Hz (Automatic change)
  - f. Frequency accuracy : within  $\pm 0.3\%$
  - g. Wave Distortion : Within 3.5% (Linear Load)
  - h. Power factor : 0.7
  - I. Crest Factor : 3:1
  - j. Green Mode : 30W or less
- 7) Performance
  - a. Efficiency : 87%TYP.
  - b. Transient Response : Within 8% (0  $\Leftrightarrow$  100% Load Step)
  - c. Transfer Time : ZERO for Line Fails or Reverse : 4mSec.  
Transfer to Bypass or Reverse

## 2. Battery specifications

- 1) Battery : Sealed Lead-Acid battery
- 2) Quantity : 4 units
- 3) Working voltage range : 48V
- 4) Recharge Time (90%) : 8hours

3. Environmental condition

- 1) Installation locatioir : Indoor
- 2) Temperature : 0 to 40°C
- 3) Humidity : 0 to 95%
- 4) Audible Noise : 45 dB(1m)

4. Mechanical

- 1) Color : Pantone 8403C
- 2) Dimension : 426 mm(W) × 502 mm(D) × 88 mm(H)
- 3) Weight : 23.2 kg

5. Heat value : 126 kcal/H

6. Insulation resistance Between current-carrying part and cabinet  
5 megohms or more with 500 VDC megger.

7. Dielectric strength Between current-carrying part and cabinet  
There shall be no abnormality at AC 50 Hz and 1.5 kV  
for 1 minute.